

SprayChalk

THE PRODUCT FOR TEMPORARY SHADING



Do you require incidental shading against excessive sunlight? Or do you require additional protection for your crop? SprayChalk was developed specifically for use during high solar radiation. The shading effect can be easily adjusted. Liquid SprayChalk is very easy to apply and is removed quickly by a few rain showers. SprayChalk can be used for temporary additional shading on ReduSol and ReduHeat.

ADVANTAGES OF LIQUID SPRAYCHALK

- Adjustable shading effects.
- Easy to mix with water.
- Prevents clogged nozzles.
- Spares the pump due to well-dispersed chalk.
- Can be removed quickly by a few rain showers.

HOW TO USE IT

Depending upon the required shading effect, dilute SprayChalk with clean water. The number of buckets required when using 2,000 litres of spraying liquid (sufficient for a 10,000 square metre surface) is shown below.

DILUTION RATIO OF SPRAYCHALK : WATER	NUMBER OF BUCKETS OF SPRAYCHALK	SHADING EFFECT (%)
1:4	16	78
1:8	9	58

- The above values were measured under laboratory conditions and serve as an indication only.
- The shading effect includes greenhouse covering materials and structural components.

Liquid SprayChalk is available in 25 kg buckets.



For more information about our products, visit www.mardenkro.com